

AVANTIX TINO SXS Suspended

SXS.FIX.7.14.TR — AVANTIX TINO SXS 7.pdf

SPECIFICATION / 规格项目	ENGLISH	中文
Mounting 安装方式	Suspended	吊装
Power 功率	≥5W	≥5W
Dimensions 外形尺寸	D70X140mm (Adjustable) · D70X200mm (Adjustable) · D70X250mm (Adjustable)	D70X140mm (Adjustable) · D70X200mm (Adjustable) · D70X250mm (Adjustable)
Cut-out 开孔尺寸	N/A	无需开孔
Beam angle 光束角	45° · 36° · 24°	45° · 36° · 24°
Colour temperature 色温	3000k · 4000k · 6000k	3000k · 4000k · 6000k
Control 控制方式	ON/OFF · DALI	ON/OFF · DALI
IP rating 防护等级	IP65	IP65
CRI 显色指数	≥90	≥90
UGR 统一眩光值	<19	<19
Efficacy 光效	≥135 Lm/W	≥135 Lm/W
Light source 光源	COB	COB
LED LED 型号	OSRAM GWKAFJB9.KM	OSRAM GWKAFJB9.KM
Optic 光学部件	Lens	透镜
Light control 出光控制	Direct	直射

Body material 灯体材质	DIE-CAST Aluminum	压铸铝
Finish 表面处理	Powder Coating	粉末喷涂
Finishes available 可选颜色	WHITE - BLACK	白色 / 黑色
Power factor 功率因数	>0.9	>0.9
Input 输入电源	AC220V, 50-60Hz	AC220V, 50-60Hz
Operating temperature 工作温度	-25°C ~ 60°C	-25°C ~ 60°C
Lifespan / warranty 寿命 / 质保	50,000h	50,000h
Driver brands 驱动品牌	EAGLERISE · EUCHIPS	EAGLERISE · EUCHIPS
Applications 应用场所	Residential · Office · Tower · Mall	住宅 · 办公 · 写字楼 · 商场

Figures as published by AVANTIX on the original product datasheet (AVANTIX TINO SXS 7.pdf).
数据取自 AVANTIX 原厂产品资料 (AVANTIX TINO SXS 7.pdf) 。
This bilingual reference sheet is generated by the distributor for Chinese-market convenience; it is not a substitute for AVANTIX's own PDF, available on the English pages of this site.
本双语参考表由经销商为方便中国市场客户查阅而生成，不能替代 AVANTIX 原版 PDF (可在本网站英文页面下载) 。